



SLAB SAVER

Concrete Finishing Aid

PRODUCT DESCRIPTION

Slab Saver by DecoCrete is an advanced finishing aid designed to simplify the concrete finishing process. **Slab Saver** extends workable time in challenging conditions such as high wind, heat, intense sun or low humidity, eliminating the need for adding water to the surface which can compromise the surface strength of the concrete slab. **Slab Saver** is ideal for working in/finishing dry shake color hardeners and makes finishing type 1L cement, high-cement, air-entrained, or silica-enhanced concrete easier. **Slab Saver** is ready-to-use right out of the bucket, and should not be diluted.

Available in 1 or 5 gallon containers.

TECHNICAL INFORMATION

- + Coverage Rate.....600 - 1200 sq. ft./gal.
- + Clean Up.....Water
- + VOC Content.....<0 g/l

RECOMMENDED APPLICATIONS

- + Type 1L Concrete
- + Smooth Finished Concrete
- + Broom Finished Concrete
- + Color Hardener



QUICK FACTS

- + Easy Finishing
- + Aids In Finishing Type 1L Concrete
- + Ready-To-Use Formula
- + Safe For Colored Concrete
- + Reduces Drag Between Finishing Tools and Concrete Surfaces
- + Great For Working In and Finishing Dry Shake Color Hardeners
- + Made In The USA



SLAB SAVER

Concrete Finishing Aid

INSTRUCTIONS FOR USE

Slab Saver is ready for use right out of the bucket. However, before each time the product is used, it should be thoroughly agitated. **DO NOT DILUTE!**

DO NOT SPRAY ON SURFACES ALREADY CONTAINING EXCESSIVE BLEED WATER!

FLOATING

Slab Saver should be used on an as-needed basis during this stage of concrete placement. If the surface of the concrete already has noticeable bleed water, it is not recommended to apply Slab Saver. However, if the surface is dry or sticky, Slab Saver significantly reduces drag between the concrete and floating tools. Mist Slab Saver as needed when bull floating at the rate of 600 - 1200 square feet per gallon and immediately work into the surface.

TROWELING

Mist Slab Saver as needed to help trowel finish the concrete at an average rate of 600 - 1200 square feet per gallon per application and work into the surface with a hand trowel or trowel machine on smooth finished floors. For broomed concrete finishes, Slab Saver can be worked in with a bull float or fresno trowel. Multiple applications may be used throughout the finishing process, however, do not exceed 600 square feet per gallon per application.

COLOR HARDENER

Slab Saver can be applied as needed, both before and after the application of dry-shake color hardeners. This is especially helpful on hot, sunny, or windy days when there is a limited amount of bleed water to "wet out" the color hardener. For these applications, Slab Saver should be applied at the rate of 600 - 1200 square feet per gallon per application.

APPLICATION

Pour Slab Saver into a pump-up sprayer or the water tanks of a ride-on trowel. If using a pump-up sprayer, keep the sprayer fully pumped up to allow for even distribution across the concrete slab. Spray Slab Saver on the surface of the concrete during floating or troweling at the recommended coverage rate, and work into the surface of the concrete immediately after application. The full benefits of Slab Saver will not be achieved if it is allowed to dry/evaporate before being worked in.

PRO TIPS

- + *Use only as needed*
- + *If you can float it, don't coat it*
- + *Do not over apply*
- + *Do not allow Slab Saver to puddle on the surface*
- + *Do not allow Slab Saver to freeze*
- + *Always make sure to work Slab Saver into the surface before it dries*



For tutorials and even more decorative concrete content, check out our YouTube channel by scanning the QR code, or check out our other social media accounts listed here.

